

EX43000 Series

Industrial Unmanaged 8-port 10/100BASE Ethernet Switch



Overview

EtherWAN's EX43000 Series is an industrial unmanaged Fast Ethernet switching platform, designed for easy deployment in industrial environments.

The EX43000 Series is equipped with eight Fast Ethernet ports, or a combination of Fast Ethernet copper ports and two 100FX ports for long distance connectivity. This versatile switch features 10/100Mbps transfer speeds, full/half-duplex auto-negotiation and auto MDI/MDIX operation allowing you to connect your network devices without hassles.

The EX43000 is feature-rich with full wire speed Fast Ethernet throughput, QoS (Quality of Service), IEEE 802.3az EEE (Energy Efficient Ethernet) and Broadcast storm protection. The EX43000 Series is built with relay alarm to notify users when power fails or link down occurs. It also supports Broadcast storm protection by enabling the DIP switch. The EX43000 Series is housed with a DIN rail mountable metal compact case which is an ideal solution for network applications in harsh environments.

EtherWAN – "When Connectivity is Crucial."

Spotlight

• Industrial Grade

- Supports -20 to 60°C (-4 to 140°F) operating temperature

• Port Failure Alarm and Broadcast Storm Protection

- Provide relay alarm to notify users when power fails or link down occurs by DIP switch
- Selectable DIP switch to set a threshold level to prevent from performance degradation or network choking

• Fiber Connectivity

- Up to two 100BASE-FX ports with SC, ST, WDM and SFP options

• Energy Efficient Ethernet (EEE)

- Supports IEEE 802.3az standard

• High Reliability

- Fanless design
- No moving parts

Hardware Specifications

Technology

Standards

- IEEE 802.3u 100BASE-TX/FX
- IEEE 802.3x full-duplex flow control
- IEEE 802.3az Energy Efficient Ethernet
- IEEE 802.1p Quality of Service (QoS)

Forward and Filtering Rate

- 14,880pps for 10Mbps
- 148,810pps for 100Mbps

Packet Buffer Memory

- 448K bits

Processing Type

- Store-and-Forward
- Auto Negotiation
- Half-duplex back-pressure and IEEE 802.3x full-duplex flow control
- Auto MDI/MDIX

Address Table Size

- 1K MAC addresses

Power

Input Voltage

- 12-48VDC (Terminal Block)

Power Consumption

- 12VDC@4.34W, 24VDC@4.57W, 48VDC@6.28W

Protection

- Reverse polarity protection

Mechanical

Casing

- Aluminum case
- IP30

Dimensions

- 43.6 x 110 x 135mm (W x D x H)
(1.74" x 4.33" x 5.31")

Weight

- 0.51Kg (1.12lbs)

Installation

- DIN-Rail (Top hat type 35mm) or Panel mounting

Interface

Ethernet Ports

- 10/100BASE-TX: 8 or 6 ports
- 100BASE-FX: 0 or 2 ports

LED Indicators

- Per Unit: Power 1 (Green), Power 2 (Green)
- Per Port: Link/Activity (Green)

DIP Switches

- Enable/Disable Port fault alarm
- Enable/Disable Broadcast Storm Protection

Alarm Contact

- One relay output with current 1A@250VAC
- Supports normal close and normal open

Environment

Operating Temperature

- -20 to 60°C (-4 to 140°F)
Tested @ -30 to 70°C (-22 to 158°F)

Storage Temperature

- -40 to 85°C (-40 to 185°F)

Ambient Relative Humidity

- 5% to 95% (non-condensing)

Regulatory Approvals

ISO

- Manufactured in an ISO 9001 facility

Safety

UL 60950

EMI

FCC Part 15B Class A

VCCI Class A

EN 61000-6-4

EN 61000-3-2

EN 61000-3-3

EN 55022 Class A

EMS

EN 61000-6-2

- EN 61000-4-2 (ESD Standards)
- EN 61000-4-3 (Radiated RFI Standards)
- EN 61000-4-4 (Burst Standards)
- EN 61000-4-5 (Surge Standards)
- EN 61000-4-6 (Induced RFI Standards)
- EN 61000-4-8 (Magnetic Field Standards)



Environmental Test Compliances

IEC 60068-2-6 Fc (Vibration)


IEC 60068-2-27 Ea (Shock)

FED STD 101C Method 5007.1 (Free fall w/package)


Dimensions




Front
EX43008




Front
EX43026




Front
EX43026



Side



Back



Bottom

Ordering Information

Model

EX43008-00-1-AA	8-port 10/100BASE-TX Industrial Unmanaged Ethernet Switch
EX43026-XY-1-AA	6-port 10/100BASE-TX +2-port 100BASE-FX Industrial Unmanaged Ethernet Switch

* DIN-Rail mounting kit included.

100FX Fiber Options (XY)

1A	Multi Mode (SC) - 2Km
1B	Multi Mode (ST) - 2Km
2A	Single Mode (SC) - 20Km
2D	Single Mode (ST) - 20Km
2E	Single Mode (SC) WDM-TX: 1310nm/RX: 1550nm-20Km
2G	Single Mode (SC) WDM-TX: 1550nm/RX: 1310nm-20Km
V	100BASE SFP

* More 100FX Fiber options also available upon request.

Optional Accessories

KP-AA96-480	Panel Mounting Kit
KR-BKEL900	Rack Mounting Kit
HDR-30-24	30W/1.5A DIN-Rail 24VDC Industrial Power Supply
HDR-60-24	60W/2.5A DIN-Rail 24VDC Industrial Power Supply
EDR-75-24	75W/3.2A DIN-Rail 24VDC Industrial Power Supply