

Industrial Ethernet Switches

PIGE 10T-4S-G



- TX Ports 8 x Gigabit PoE+, 2 x 10/100/1000
- Fibre Ports 4 x 100 / 1000 SFP Ports
- L2+ Features provide better management, security, 802.1Q VLAN mirroring, Port Isolation, IGMP Snooping, DHCP Snooping, LLDP, PoE+ Management, IP Source Guard, ARP Inspection, Access Control Lists
- STP (802.1D) and RSTP (802.1W)
- Jumbo frame support up to 9.6 Kilobytes
- Support enhanced management through WEB, CLI, TELNET, SSH, SNMP
- Cable diagnostics
- Support IEEE802.3af and 802.3at and cable PoE configuration
- G.8032 support <50ms ring protection
- 48vdc (48-57vdc) dual redundant power supply using 6-pin 5.08mm-gap plug-in terminal

Technical Specifications	
Product name	PIGE 10T 4S-G (14 Port Managed Gigabit PoE Switch)
Performance and switching capacity	
Capacity in millions of packets per second	20.83mpps
Switching Capacity	256 Gbps
Interfaces	
Ports	14 Ports – 8 Gig Tx PoE+, 2xGig Tx, 4 x 100/1000 SFP Ports
Layer 2 Switching	
STP / RSTP	Spanning Tree Protocol 802.1d, Rapid Spanning Tree Protocol (802.1w)
G.8032 ERPS	<50ms ring protection
Aggregation	LACP (Link Aggregation Protocol Protocol) IEEE 802.3ad up to 7 groups, 14 ports per group
VLAN	Up to 4K simultaneously VLAN (out of 4096 VLAN ID's) Port based / Tag based
IGMP v1 / v2	IGMP limits bandwidth hungry multicast traffic allowing only the requester to receive the data. Support for 1024 multicast groups .
Security	
SSH Secure Shell	SSH Secures Telnet traffic in or out of the switch, SSHv1, & v2 supported
Secure socket layer (SSL) HPPTS	SSL Encrypts the HTTP traffic, allowing advance secure access to the browser-based management GUI in the switch
Port Security	Locks Mac Addresses to ports, and limits the number of learned MAC Addresses
DHCP Snooping	Prevent unauthorised configuration and use of IP Addresses providing support for IP Source Guard and ARP detection
IP Source Guard	Prevents datagrams with spoofed addresses from entering the network
ARP Inspection	Prevents ARP Spoofing attacks and ARP
Storm Control	Prevents broadcast, multicast or unicast storms on a port.
ACL	Support for 256 entries. Drop or rate limitation based on source and destination MAC, VLAN ID or IP address protocol, DSCP / IP Precedence, TCP / UDP Source and Destination ports, 802.1p priority, Ethernet type, Internet Control Message Protocol (ICMP), IGMP packets TCP Flags

Quality of Service	
Hardware	Support for 8 hardware queues
Scheduling	8 Class of Service per port strict priority and weighted round-robin (WRR)
Classification	Ingress policy; egress shaping ,and rate control per VLAN per port, and flow based.
Management and diagnostics	
Web Gui Interface	Built in switch configuration, for browser-based device configuration (HTTP / HTTPS) Supports configuration, system dashboard, maintenance and monitoring
Dual Image	Dual Image provides independent primary and secondary files for backup during upgrades
Firmware Upgrade	Web Browser upgrade via (HTTP / HTTPS), TFTP and via console port
Port mirroring	Monitoring of a port via second port, using a network analyser or RMON Probe
Other management	Single IP address for management (HTTP / HTTPS); SSH: RADIUS, DHCP Client, SNMP, Cable diagnostics; Ping; system log; Telnet client (SSH Secure Support)
Green Ethernet	
Green and Energy-Saving Ethernet (EEE)	Compliant with IEEE802.3az Energy Efficient Ethernet Task Force. Automatically turns off power on the Gigabit Ethernet RJ-45 ports when detecting the link is down or the client is idle. Active mode is resumed without the loss of any packets when the switch detects the link is up.
Cable Length Detection	The switch adjusts the signal strength based on the cable length. Reduced power for shorter length cable
General	
Jumbo Frames	Frame Size up to 9KB supported
MAC Table	Up to 8K MAC Addresses
LLDP	Link layer discovery protocol used by network devices to advertise their identities, capabilities, and neighbours on an IEEE 802.3 local area network
PoE	
PoE Standards	IEEE802.3af Power Per Port 15 watts IEEE802.3at Power per port 30 watts
PoE Ports	8 PoE ports end-span
Minimum Requirements	
Browser	Internet Explorer v6 or later, Mozilla Firefox version 2.5 or later
Environmental	
Dimensions	165 x 148 x 54mm
Weight	1.1Kg
Temperature	Operating Temperature -40c ~ +80C: Storage Temperature -40C~+85C
Humidity	Operating Humidity 10% to 90% relative non-condensing
Certification and Standards	
EMC	FCC Part 5, CE-EMC / LVD EN 55024 :2010+A1 :2015, EN61000-3-2:2014, EN 61000-3-3:2013 EN61000-4-2 (ESD), EN61000-4-3(RS). EN61000-4-4 (EFT), EN61000-4-5 (Surge) EN61000-4-6 (CS), EN61000-4-8, EN 61000-4-11, EN 55032:2015/AC:2016-07
Vibration	IEC 60068-4-11

Ordering Information	Description
PIGE 10T 4S-G	Industrial Ethernet Switch, 8 x Gig PoE+ Ports, 2 x Gig Tx Ports, 4 x Gig SFP ports, SNMP Management -40C ~ +80C