

EKI-7710G-2CP EKI-7710G-2CPI

8G+2G Port Gigabit Managed Redundant Industrial PoE Switch



Features

- 8 x IEEE 802.3 af/at PoE Gigabit ports + 2 x Gigabit copper/SFP combo ports
- SFP socket for easy and flexible fiber expansion
- Redundancy: X-Ring Pro (ultra-high-speed recovery time, <20 ms), RSTP/STP (802.1w/1D)
- IXM function enables fast deployment
- Security: 802.1x (port-based, MD5/TLS/TTLS/PEAP encryption), RADIUS
- Management: SNMP v1/v2c/v3, WEB, Telnet, standard MIB, private MIB
- NEMA TS2 for traffic control
- EN50121-4 approval for railway trackside deployment
- Dual 24 ~ 48 V_{DC} power input and 1 x relay output
- Wide operating temperature range of -40 ~ 75°C (EKI-7710G-2CPI)

Introduction

The EKI-7710G-2CP/2CPI support 8 Gigabit PoE ports and 2 Gigabit combo ports. They provide up to 30W per port for high-power-consumption powered devices. They come embedded with Advantech IXM function, which can benefit users with fast deployment and can dramatically save considerably on engineering time and costs. The EKI-7710G series also support NMS to help IT managers with networking maintenance and failure prevention. Finally, they are equipped with X-Ring Pro, which can achieve ultra-high-speed recovery times of <20 ms, thus ensuring network stability.

Specifications

Interface

- I/O Port** 8 x 10/100/1000BASE-T/TX RJ-45
2 x RJ-45/SFP(mini-GBIC)Combo port
- Console port** RS-232 (RJ45)
- Power Connector** 6-pin screw Terminal Block (including relay)

Physical

- Enclosure** Metal Shell
- Protection Class** IP 30
- Installation** DIN-Rail
- Dimensions (W x H x D)** 74 x 152 x 105 mm (2.91" x 5.98" x 4.13")

LED Display

- System LED** PWR1, PWR2, SYS, CFG, Alarm and R.M.
- Port LED** Link / Speed / Activity / PoE

Environment

- Operating Temperature** -40 ~ 75°C (-40 ~ 167°F) 7710G-2CPI
-10 ~ 60°C (-40 ~ 140°F) 7710G-2CP
- Storage Temperature** -40 ~ 85°C
- Ambient Relative Humidity** 10 ~ 95% (non-condensing)
- Humidity** 10 ~ 95% (non-condensing)

Power

- Power Consumption** 12.1W @ 48V_{DC} (System)
- Power Input** 24 ~ 48 V_{DC}, redundant dual power input
- Power Budget** 120W
- Fault Output** 1 Relay Output

Certification

- EMI** CE, FCC Class A
- Safety** UL508
UL60950*, C1D2*
- EMC** EN 61000-4-2
EN 61000-4-3
EN 61000-4-4
EN 61000-4-5
EN 61000-4-6
EN 61000-4-8
EN50121-4*
- Shock** IEC 60068-2-27
- Freefall** IEC 60068-2-32
- Vibration** IEC 60068-2-6
- Traffic Control** NEMA TS2*

*= Compliant


- Patent** <http://www.advantech.com/legal/patent>

L2 Features

- L2 MAC Address** 8K
- Jumbo Frame** 9216 Bytes
- VLAN Group** 256 (VLAN ID 1 ~ 4094)
- VLAN Arrange** Port based VLAN, Q-in-Q (VLAN Stacking), GVRP
- Port Mirroring** Per port, Multi-source port,
- IP Multicast** IGMP Snooping v1/v2/v3, MLD Snooping, IGMP Immediate leave
- Storm Control** Broadcast, Multicast, Unknown unicast
- Redundancy** IEEE 802.1D-STP, IEEE 802.1s-MSTP, IEEE 802.1w-RSTP, X-Ring Pro, with ultra high-speed recovery time less than 20ms

Dimensions

Unit: mm [inch]



Panel Cut-out Dimensions: 105 (4.137) x 152 (5.984) x 74 (2.91)

QoS

- **Priority Queue Scheduling** WRR (Weighted Round Robin), SP (Strict Scheduling Priority) Hybrid Priority
- **Class of Service** IEEE 802.1p Based CoS, IP TOS, DSCP based CoS
- **Rate Limiting** Ingress Rate limit, Egress Rate limit
- **Link Aggregation** IEEE 802.3ad Dynamic Port Trunking, Static Port Trunking

Security

- **Port Security** Static, Dynamic IP Source Guard, ARP Spoofing Prevention, Access Control List, DHCP Snooping,
- **Authentication** 802.1x (Port-Based, MD5/TLS/TTLS/PEAP Encryption), TACACS+

Management

- **DHCP** Client, Server, Option66/67/82
- **Access** SNMP v1/v2c/v3, WEB, Telnet, RMON, Standard MIB, Private MIB
- **Security access** SSH2.0, SSL
- **Software upgrade** TFTP, HTTP, Dual Image
- **NTP** SNTP client

Ordering Information

- **EKI-7710G-2CPI-BE** 8GE + 2G Combo Port Managed PoE Ethernet Switch w/Wide Temp

Note: For SFP copper type, only 1000Mbps supported.