


EKI-2525PA EKI-2528PAI

5-Port Industrial PoE Switch with 24/48 V_{DC} Power Input

8-Port Industrial PoE Switch with 24/48 V_{DC} Power Input and Wide Temperature



Features

- 5/8 x fast Ethernet ports with 4 x PoE ports with injector function
- Supports 10/100 Mbps auto negotiation
- Provides broadcast storm protection
- Ethernet ESD protection
- Power line EFT protection
- Slim size, DIN rail/wall mount options
- IP30-rated enclosure
- Redundant 24/48 V_{DC} power input and P-Fail relay
- Operating temperatures of -10 to 60°C (EKI-2525PA) and -40 ~ 75°C (EKI-2528PAI)

Introduction

The EKI-2525PA and EKI-2528PAI are 5/8-port unmanaged PoE industrial Ethernet switches with 4 PoE ports classified as power source equipment. These PoE switches realize a centralized power supply, providing up to 15.4 W of power per port. Advantech EKI PoE switches can be implemented to power IEEE 802.3af-compliant powered devices via Ethernet cable, thus eliminating the need for additional wiring. Advantech EKI PoE switches come equipped with all the standard features of the EKI family. Furthermore, they offer a 24/48 VDC redundant power input design and are secured with a double protection mechanism: power polarity reverse protect and an overload current resettable fuse. Advantech EKI PoE devices come with an IP30-rated compact metal housing to protect against dust in industrial environments.

Specifications

Communications

- **Standard** IEEE 802.3, 802.3u, 802.3x, 802.3af
- **LAN** 10/100BASE-TX
- **Transmission Distance** Up to 100 m
- **Transmission Speed** Up to 100 Mbps

Interface

- **Connectors** PoE Ports: 4 (Ports 1 ~ 4)
Ethernet ports: 1 (Port 5 ~ Port 8), EKI-2525PA
Ethernet ports: 4 (Port 5 ~ Port 8), EKI-2528PAI
6-pin removable screw terminal (power & relay)
- **LED Indicators** P1, P2, P-Fail
10/100TX: Link/Activity, Duplex/Collision

Power

- **Power Consumption** EKI-2525PA: 62.5 W (Full load PoE)
EKI-2528PAI: 65 W (Full load PoE)
- **Power Input** 24/48 V_{DC}, redundant dual inputs
- **Power Output** 15.4 W at 48 V (per PoE port)
- **Fault Output** 1 Relay Output

Mechanism

- **Dimensions (W x H x D)** 48.6 x 140 x 95 mm (1.91" x 5.51" x 3.74")
- **Enclosure** IP30, Metal shell with solid mounting kits
- **Mounting** DIN-rail, Wall

Protection

- **Reverse Polarity** Present
- **Overload current** Present

Environment

- **Operating Temperature** -10 ~ 60°C (14 ~ 140°F) (EKI-2525PA)
Wide temp. model -40 ~ 75°C (-40 ~ 167°F) (EKI-2528PAI)
- **Storage Temperature** -40 ~ 85°C (-40 ~ 185°F)
- **Operating Humidity** 5 ~ 95% (non-condensing)
- **Storage Humidity** 0 ~ 95% (non-condensing)
- **MTBF** EKI-2525PA: 196,813 hours
EKI-2528PAI: 241,413 hours


Certification

- **Safety** UL508
- **EMI** FCC Part 15 Subpart B Class A, EN 55022 Class A
- **EMS** EN 61000-4-2
EN 61000-4-3
EN 61000-4-4
EN 61000-4-5
EN 61000-4-6
EN 61000-4-8
- **Shock** IEC 60068-2-27
- **Freefall** IEC 60068-2-32
- **Vibration** IEC 60068-2-6
- **Patent** <http://www.advantech.com/legal/patent>

Dimensions


Unit: mm [inch]

EKI-2525PA



Panel Cut-out Dimensions: 104 x 140 x 48.6 mm (4.1" x 5.52" x 1.91")

EKI-2528PAI



Panel Cut-out Dimensions: 104 x 140 x 48.6 mm (4.1" x 5.52" x 1.91")

Ordering Information

- EKI-2525PA 5-port Switch with 4 port-PoE and 24/48 V_{DC} Power Input
- EKI-2528PAI 8-port Switch with 4 port-PoE and 24/48 V_{DC} Power Input (Wide Temp)