

EKI-7708E-4FP EKI-7708E-4FPI

4FE+4G SFP Port Managed Redundant Industrial PoE Switch



Features

- 4 x Fast Ethernet ports + 4 x SFP ports
- Support 4 x IEEE 802.3at/af PoE ports for PD demands
- Redundancy: X-Ring Pro (ultra-high-speed recovery time, <20 ms), RSTP/STP (802.1w/1D)
- IXM function for fast deployment
- Security Pack with 802.1X, ACL, RADIUS, TACACS+, MAB Authentication, SNMPv3, HTTPS, SSH, and SFTP
- Management: SNMP v1/v2c/v3, WEB, Telnet, standard MIB, private MIB
- Supports NMS for easy and visualized to monitor and manage network remotely
- Dual 48 V_{DC} power input and 1 x relay output

Introduction

The EKI-7708E-4FP/4FPI provide 4 fast Ethernet IEEE 802.3 at/af PoE ports and 4 SFP (mini-GBIC) ports. They can provide up to 30 W per port to fulfill high-power-consumption power device requirements. They are embedded with Advantech's IXM function, which can benefit users with fast deployment and can save considerably on engineering time and costs. The EKI-7708E series also support NMS to help IT managers with networking maintenance and failure prevention. Finally, they are equipped with X-Ring Pro, which can achieve ultra-high-speed recovery times of <20 ms, thus ensuring network stability. The EKI-7708E-4FPI in particular also features a wide operating temperature range of -40 ~ 75°C and NEMA TS2 rating, making it ideal for use in traffic applications. Finally, the EKI-7708E-4FP/4FPI meet the EN50121-4 European railway standard requirements for emissions and railway platform and trackside deployment.

Specifications

Interfaces / Communications

- **I/O Port** 4 x 10/100BASE-T/TX RJ-45
4 x SFP (mini-GBIC) port
Auto-Negotiation, Full/Half Duplex Mode
Auto MDI/MDI-X Connection
- **Standards** IEEE 802.3 for 10BaseT
IEEE 802.3u for 100BaseT(X)/FX
IEEE 802.3z for 1000BaseSX/LX/LHX/ZX
IEEE 802.3x for Flow Control
- **PoE** Port 1 ~ Port 4: IEEE 802.3at/af
- **Console Port** RS-232 (RJ45)
- **Power Connector** 6-pin screw Terminal Block (including relay)

Physical

- **Enclosure** Metal Shell
- **Protection Class** IP 30
- **Installation** DIN-Rail, Wall-mount
- **Dimensions (W x H x D)** 74 x 152 x 105 mm (2.91" x 5.98" x 4.13")

LED Indicators

- **System LED** PWR1, PWR2, SYS, Alarm and R.M.
- **Port LED** Link / Speed / Activity / PoE

Environment

- **Operating Temperature** -40 ~ 75°C (-40 ~ 167°F) (EKI-7708E-4FPI)
-10 ~ 60°C (-40 ~ 140°F) (EKI-7708E-4FP)
- **Storage Temperature** -40 ~ 85°C (-40 ~ 185°F)
- **Ambient Relative Humidity** 5 ~ 95% (non-condensing)
- **Overload Current Protection** Present
- **Reverse Polarity Protection** Present
- **MTBF** 910,074 hours

Power

- **Power Consumption** 12.1W @ 48V_{DC} (System)
- **Power Input** 48 V_{DC} (46 to 57 V_{DC})
53 ~ 57 V_{DC} is recommended for 802.3at
redundant dual power input
- **Power Budget** 120W
- **Fault Output** 1 Relay Output

Certification


- **Safety** UL 61010-2-201
- **EMI** CE, CISPR 32, FCC Part 15B Class A
- **EMS** IEC 61000-4-2
IEC 61000-4-3
IEC 61000-4-4
IEC 61000-4-5
IEC 61000-4-6
IEC 61000-4-8
IEC 61000-4-11
- **EMC** EN 61000-6-2
EN 61000-6-4
- **Shock** IEC 60068-2-27
- **Freefall** IEC 60068-2-32
- **Vibration** IEC 60068-2-6
- **Traffic control** NEMA TS-2
- **Railway Trackside** EN 50121-4

Switch Properties

- **Switch Capacity** 8.8Gbps
- **Transmission Rate** 6.55Mpps
- **MAC Table Size** 8K
- **Jumbo Frame** 1,0240 Bytes
- **Packet Buffer Size** 4.1Mb
- **Max. IGMP Group** 256
- **Max. VLAN Group** 256 (VLAN ID 1 ~ 4094)

Dimensions

Unit: mm [inch]



Panel Cut-out Dimensions (W x H x D): 74 x 152 x 105 mm (2.913 x 5.98 x 4.134 inch)

L2 Features

- VLAN Arrange**
 - Port Mirroring**
 - RSPAN**
 - GARP**
 - IP Multicast**
 - Storm Control**
 - LLDP**
 - Industrial Protocol**
 - Redundancy**
- 802.1Q Tag-based VLAN, 802.1ad QinQ VLAN Stacking
1 to 1, N to 1
Max. Mirror Session: 4
Remote Switched Port Analysis
GVRP, GMRP
IGMP Snooping v1/v2/v3, MLD Snooping, IGMP Immediate leave
Broadcast, Multicast, Unknown unicast
802.1ab LLDP, LLDP-MED
Modbus/TCP
IEEE 802.1D-STP, IEEE 802.1s-MSTP, IEEE 802.1w-RSTP, X-Ring Pro, with ultra high-speed recovery time less than 20ms, ERPS(G.8032)

QoS

- Priority Queue Scheduling**
 - Class of Service**
 - Rate Limiting**
 - Link Aggregation**
- WRR (Weighted Round Robin), SP (Strict Scheduling Priority) Hybrid Priority, Max. Priority Queues: 8
IEEE 802.1p Based CoS, IP TOS, DSCP based CoS
Ingress Rate limit, Egress Rate limit
IEEE 802.3ad Dynamic Port Trunking, Static Port Trunking

Security

- Port Security**
 - 802.1X**
 - MAB**
 - Authentication**
 - IP Security**
 - ACL**
- Static/Dynamic MAC, Max. Learning Limit, MAC Violation Notice
Port-based/MAC-based Authentication (MD5/PEAP/TLS/TTLS Encryption)
MAC Authentication Bypass
RADIUS, TACAS+
IP Source Guard, DHCP Snooping, ARP Spoofing Prevention
Access Control List (IP-ACL, MAC-ACL)
Max. ACL Entries: 128

Management

- PoE**
 - DHCP**
 - Access**
 - Security Access**
 - Software Upgrade**
 - NTP**
- PoE system settings, port settings and status
Client, Server, Option66/67/82, DHCP Relay
SNMP v1/v2c/v3, WEB, Telnet, RMON, Standard MIB-II, Private MIB, Ethernet-Like MIB, RMON MIB (Group 1, 2, 3, 9)
SSH2.0, SSL
TFTP, SFTP, HTTP, Dual Image
SNTP client

Ordering Information

- EKI-7708E-4FPI-AE** 4FE + 4G SFP Port Managed PoE Ethernet Switch w/ Wide Temp
- EKI-7708E-4FP-AE** 4FE + 4G SFP Port Managed PoE Ethernet Switch

Note: For SFP copper type, only 1000Mbps supported.