




## HIRSCHMANN

A BELDEN BRAND

### Product information M-SFP-LX+/LC EEC

Industrial Ethernet: System Accessories: Fiberoptic Transceiver: SFP Gigabit-Ethernet Transceiver for media module: M-SFP-LX+/LC EEC

Name	M-SFP-LX+/LC EEC
	
	SFP Fiberoptic Gigabit Ethernet Transceiver, extended temperature range.
<b>Delivery informations</b>	
Availability	available
<b>Product description</b>	
Description	SFP Fiberoptic Gigabit Ethernet Transceiver, extended temperature range.
Port type and quantity	1 x 1000BASE-LX with LC connector
Type	M-SFP-LX+/LC EEC
Order No.	942 024-001
<b>Network size - length of cable</b>	
Multimode fiber (MM) 50/125 µm	n/a
Multimode fiber (MM) 62.5/125 µm	n/a
Single mode fiber (SM) 9/125 µm	5-42 km, 5-20 dB link budget at 1310 nm, A = 0.4 dB/km, 3 dB reserve
Single mode fiber (LH) 9/125 µm (long haul transceiver)	n/a
<b>Power requirements</b>	
Operating voltage	power supply via the switch
Power consumption	1 W
<b>Service</b>	
Diagnostics	optical input and output power, transceiver temperature
<b>Ambient conditions</b>	
Operating temperature	-40°C to +85°C
Storage/transport temperature	-40°C to +85°C
Relative humidity (non-condensing)	10% up to 95%
MTBF	856 years, Telcordia SR-332
<b>Mechanical construction</b>	
Dimensions (W x H x D)	20 mm x 18 mm x 50 mm
Mounting	SFP slot
Weight	40 g
Protection class	IP 20
<b>Mechanical stability</b>	
IEC 60068-2-27 shock	15 g, 11 ms duration, 18 shocks
IEC 60068-2-6 vibration	1 mm, 2 Hz - 13.2 Hz, 90 min.; 0.7g, 13.2 Hz - 100 Hz, 90 min.; 3.5 mm, 3 Hz - 9 Hz, 10 cycles, 1 octave/min.; 1g, 9 Hz - 150 Hz, 10 cycles, 1 octave/min.
<b>EMC interference immunity</b>	
EN 61000-4-2 electrostatic discharge (ESD)	6 kV contact discharge, 8 kV air discharge
EN 61000-4-3 electromagnetic field	10 V/m (80 - 1000 MHz)
EN 61000-4-4 fast transients (burst)	2 kV power line, 1 kV data line
EN 61000-4-5 surge voltage	power line: 2 kV (line/earth), 1 kV (line/line), 1kV data line
EN 61000-4-6 conducted immunity	3 V (10 kHz - 150 kHz), 10 V (150 kHz - 80 MHz)
<b>EMC emitted immunity</b>	
FCC CFR47 Part 15	FCC CFR47 Part 15 Class A
EN 55022	EN 55022 Class A
<b>Scope of delivery and accessories</b>	
Scope of delivery	SFP module



**HIRSCHMANN**

A **BELDEN** BRAND

The information published in the websites has been compiled as carefully as possible. It is subject to alteration without notice in technical as well as in price-related/commercial respect. The complete information and data were available on user documentation. Mandatory information can only be obtained by a concrete query.