



Part Number: RPS 90/48V LV, PoE-Power Supply
48 V DC rail power supply unit

Product Description

48 V DC rail power supply unit

Technical Specifications

Product description

Type:	RPS 90/48V LV
Part Number:	943 980-001

More Interfaces

Voltage input:	1 x terminal block, 2-pin
Voltage output:	1 x terminal block, 4-pin

Power requirements

Current consumption:	24 V DC (4,2 A), 48 V DC (2,1 A)
Input voltage:	18 V DC to 60 V DC
Operating Voltage:	24 V DC
Output current:	1.9 A static at 48 V nominal
Redundancy functions:	redundant power supply
Activation Current:	15 A

Power Output

Output voltage:	48 - 54 V DC (typ. 48 V); externally adjustable
-----------------	---

Software

Diagnostics:	LED (green)
--------------	-------------

Ambient conditions

MTBF (MIL-HDBK 217F: Gb 25 °C):	1878940 h
Operating temperature:	-25+60 °C
Storage/transport temperature:	-40+85 °C
Relative humidity (non-condensing):	5-95 %

Mechanical construction

Dimensions (WxHxD):	60 mm x 137 mm x 115 mm
Weight:	770 g
Mounting:	DIN Rail
Protection class:	IP30

Mechanical stability

IEC 60068-2-6 vibration:	Operating: 4 ... 500Hz 1,5g
IEC 60068-2-27 shock:	15 g, 11 ms duration

EMC interference immunity

EN 61000-4-2 electrostatic discharge	± 6 kV contact discharge; ± 8 kV air discharge
EN 61000-4-3 electromagnetic	10 V/m (80 MHz ... 3000 MHz)
EN 61000-4-4 fast transients	4 kV power
EN 61000-4-5 surge	line power lines: 2 kV (line/earth), 1 kV (line/line)
EN 61000-4-6 Conducted Immunity:	10 V (150 kHz .. 80 MHz)

Approval

Basis	CE,
Standard	EN 601350-3
Safety of industrial control	EN 60950-1
Safety of information technology	CUL 60950-1
Employment in	(pending)
Hazardous	ISA 12.12.01 Class 1 Div. 2
Shipbuilding	(pending)
	Germanischer Lloyd,
	ABS
Substation	IEC 61850-3, IEEE 1813
Railway norm:	EN50121-4

Scope of delivery and

Scope of delivery:	Rail Power Supply, Description and operating manual, 1 x terminal block, 2-pin, 1 x terminal block, 4-pin
--------------------	---

Variant

Item	Typ
94398000	RPS90/48V
1	LV