

## Product information BAT-Controller WLC25

Industrial Ethernet:Industrial Wireless LAN:Chassis:BAT-Management:BAT-Controller WLC25  
<https://www.e-catalog.beldensolutions.com:443/link/57078-24455-49859-24497-118024-144719/en/conf/ui/state>

<b>Name</b>	<b>BAT-Controller WLC25</b>
	
	Central Firmware deployment and management of the Access Points. Requires an external web server.
<b>Delivery informations</b>	
<b>Availability</b>	available
<b>Product description</b>	
<b>Description</b>	Central Firmware deployment and management of the Access Points. Requires an external web server.
<b>Port type and quantity</b>	4 individual Ethernet ports 10/100/1000 Mbps
<b>Type</b>	BAT-Controller WLC25
<b>Order No.</b>	942 034-001
<b>Managed Access Points</b>	25
<b>More Interfaces</b>	
<b>Power supply/signaling contact</b>	Internal power supply unit (110–230 V, 50-60 Hz)
<b>Hardware requirements</b>	
<b>Network</b>	OpenBAT, BAT54 and BAT300 access points
<b>Mechanical construction</b>	
<b>Housing</b>	Robust metal housing, 19" 1 HU, with removable mounting brackets, network connectors on the front
<b>Ambient conditions</b>	
<b>Operating temperature</b>	5 °C ... 40 °C
<b>Relative humidity (non-condensing)</b>	0 % ... 95 %
<b>Dimensions (W x H x D)</b>	435 x 45 x 207 mm
<b>Weight</b>	3800 g
<b>Scope of delivery and accessories</b>	
<b>Scope of delivery</b>	CD including firmware, management software (LANconfig, LANmonitor, WLANmonitor) and documentation. Printed Installation Guide. 1 serial configuration cable (1.5 m), 1 Ethernet cable, 1 Cable IEC power cord (3 m), return voucher, 19 Inch DIN rail adapter

## Product information BAT-Controller WLC50

Industrial Ethernet:Industrial Wireless LAN:Chassis:BAT-Management:BAT-Controller WLC50

<https://e-catalog.beldensolutions.com:443/link/57078-24455-49859-24497-118024-144715/en/conf/uistate>

Name	BAT-Controller WLC50
	
	Central Firmware deployment and management of the Access Points. Requires an external web server.
<b>Delivery informations</b>	
Availability	available
<b>Product description</b>	
Description	Central Firmware deployment and management of the Access Points. Requires an external web server.
Port type and quantity	4 individual Ethernet ports 10/100/1000 Mbps
Type	BAT-Controller WLC50
Order No.	942 034-002
Managed Access Points	50
<b>More Interfaces</b>	
Power supply/signaling contact	Internal power supply unit (110–230 V, 50-60 Hz)
<b>Hardware requirements</b>	
Network	OpenBAT, BAT54 and BAT300 access points
<b>Mechanical construction</b>	
Housing	Robust metal housing, 19" 1 HU, with removable mounting brackets, network connectors on the front
<b>Ambient conditions</b>	
Operating temperature	5 °C ... 40 °C
Relative humidity (non-condensing)	0 % ... 95 %
Dimensions (W x H x D)	435 x 45 x 207 mm
Weight	3800 g
<b>Scope of delivery and accessories</b>	
Scope of delivery	CD including firmware, management software (LANconfig, LANmonitor, WLANmonitor) and documentation. Printed Installation Guide. 1 serial configuration cable (1.5 m), 1 Ethernet cable, 1 Cable IEC power cord (3 m), return voucher, 19 Inch DIN rail adapter

## Product information BAT-Controller WLC100

Industrial Ethernet:Industrial Wireless LAN:Chassis:BAT-Management:BAT-Controller WLC100

<https://e-catalog.beldensolutions.com:443/link/57078-24455-49859-24497-118024-144714/en/conf/uistate>

<b>Name</b>	BAT-Controller WLC100
	
	Central Firmware deployment and management of the Access Points. Requires an external web server.
<b>Delivery informations</b>	
<b>Availability</b>	available
<b>Product description</b>	
<b>Description</b>	Central Firmware deployment and management of the Access Points. Requires an external web server.
<b>Port type and quantity</b>	4 individual Ethernet ports 10/100/1000 Mbps
<b>Type</b>	BAT-Controller WLC100
<b>Order No.</b>	942 034-003
<b>Managed Access Points</b>	100
<b>More Interfaces</b>	
<b>Power supply/signaling contact</b>	Internal power supply unit (110–230 V, 50-60 Hz)
<b>Hardware requirements</b>	
<b>Network</b>	OpenBAT, BAT54 and BAT300 access points
<b>Mechanical construction</b>	
<b>Housing</b>	Robust metal housing, 19" 1 HU, with removable mounting brackets, network connectors on the front
<b>Ambient conditions</b>	
<b>Operating temperature</b>	5 °C ... 40 °C
<b>Relative humidity (non-condensing)</b>	0 % ... 95 %
<b>Dimensions (W x H x D)</b>	435 x 45 x 207 mm
<b>Weight</b>	3800 g
<b>Scope of delivery and accessories</b>	
<b>Scope of delivery</b>	CD including firmware, management software (LANconfig, LANmonitor, WLANmonitor) and documentation. Printed Installation Guide. 1 serial configuration cable (1.5 m), 1 Ethernet cable, 1 Cable IEC power cord (3 m), return voucher, 19 Inch DIN rail adapter