


Product information SPIDER 1TX/1FX

Industrial Ethernet:Unmanaged Industrial Ethernet Switches:SPIDER-Switches:SPIDER 1TX/1FX

Name		SPIDER 1TX/1FX
		
		Entry Level Industrial ETHERNET Rail Switch, store and forward switching mode, Ethernet and Fast-Ethernet (10/100 Mbit/s)
Delivery informations		
Availability	available	
Product description		
Description	Entry Level Industrial ETHERNET Rail Switch, store and forward switching mode, Ethernet and Fast-Ethernet (10/100 Mbit/s)	
Port type and quantity	1 x 10/100BASE-TX, TP cable, RJ45 sockets, auto-crossing, auto-negotiation, auto-polarity 1 x 100BASE-FX, MM cable, SC sockets	
Type	SPIDER 1TX/1FX	
Order No.	943 890-001	
More Interfaces		
Power supply/signaling contact	1 plug-in terminal block, 3-pin, no signal contact	
Network size - length of cable		
Twisted pair (TP)	0 - 100m	
Multimode fiber (MM) 50/125 µm	0 - 5000 m, 8 dB link budget at 1300 nm, A = 1 dB/km, 3 dB reserve, B = 800 MHz x km	
Multimode fiber (MM) 62.5/125 µm	0 - 4000 m, 11 dB Link budget at 1300 nm, A = 1 dB/km, 3 dB reserve, B = 500 MHz x km	
Network size - cascading		
Line - / star topology	Any	
Power requirements		
Operating voltage	9,6 V DC - 32 V DC	
Current consumption at 24 V DC	Max. 130 mA	
Power consumption	Max. 3,0 W 10,2 Btu (IT)/h at 24 V DC	
Service		
Diagnostics	LEDs (power, link status, data, data rate)	
Ambient conditions		
Operating temperature	0 °C to +60 °C	
Storage/transport temperature	-40 °C to +70 °C	
Relative humidity (non-condensing)	10% to 95%	
MTBF	128.1 years; MIL-HDBK 217F: Gb 25 °C	
Mechanical construction		
Dimensions (W x H x D)	25 mm x 114 mm x 79 mm	
Mounting	DIN Rail 35 mm	
Weight	105 g	
Protection class	IP 30	
Mechanical stability		
IEC 60068-2-27 shock	15 g, 11 ms duration, 18 shocks	
IEC 60068-2-6 vibration	3.5 mm, 3 Hz - 9 Hz, 10 cycles, 1 octave/min.; 1g, 9 Hz - 150 Hz, 10 cycles, 1 octave/min.	
EMC interference immunity		
EN 61000-4-2 electrostatic discharge (ESD)	6 kV contact discharge, 8 kV air discharge	
EN 61000-4-3 electromagnetic field	10 V/m (80 - 1000 MHz)	
EN 61000-4-4 fast transients (burst)	2 kV power line, 4 kV data line	



HIRSCHMANN

A BELDEN BRAND

Industrial Ethernet:Unmanaged Industrial Ethernet Switches:SPIDER-Switches:SPIDER 1TX/1FX

EN 61000-4-5 surge voltage	Power line: 2 kV (line/earth), 1 kV (line/line), 1 kV data line
EN 61000-4-6 conducted immunity	10 V (150 kHz - 80 kHz)
EMC emitted immunity	
FCC CFR47 Part 15	FCC CFR47 Part 15 Class A
EN 55022	EN 55022 Class A
Approvals	
Safety of industrial control equipment	cUL 508
Scope of delivery and accessories	
Scope of delivery	Device, terminal block, operating manual
Accessories to order separately	Rail power supply RPS 15, RPS 30, RPS 80 EEC or RPS 120 EEC, 19" installation frame

The information published in the websites has been compiled as carefully as possible. It is subject to alteration without notice in technical as well as in price-related/commercial respect. The complete information and data were available on user documentation. Mandatory information can only be obtained by a concrete query.