

## Product information SPIDER 3TX-TAP

Industrial Ethernet:Unmanaged Industrial Ethernet Switches:SPIDER-Switches:SPIDER 3TX-TAP

<b>Name</b>		SPIDER 3TX-TAP
		
		Entry Level Industrial ETHERNET Rail Switch, store and forward switching mode, Ethernet and Fast-Ethernet (10/100 Mbit/s)
<b>Delivery informations</b>		
<b>Availability</b>	available	
<b>Product description</b>		
<b>Description</b>	Entry Level Industrial ETHERNET Rail Switch, store and forward switching mode, Ethernet and Fast-Ethernet (10/100 Mbit/s)	
<b>Port type and quantity</b>	3 x 10/100BASE-TX, TP cable, RJ45 sockets, auto-crossing, auto-negotiation, auto-polarity	
<b>Type</b>	SPIDER 3TX-TAP	
<b>Order No.</b>	943 899-001	
<b>More Interfaces</b>		
<b>Power supply/signaling contact</b>	1 plug-in terminal block, 3-pin, no signal contact	
<b>Network size - length of cable</b>		
<b>Twisted pair (TP)</b>	0 - 100 m	
<b>Network size - cascadiability</b>		
<b>Line - / star topology</b>	Any	
<b>Power requirements</b>		
<b>Operating voltage</b>	9,6 V DC - 32 V DC	
<b>Current consumption at 24 V DC</b>	Max. 100 mA	
<b>Power consumption</b>	Max. 2,2 W 7,5 Btu (IT)/h bei 24 V DC	
<b>Service</b>		
<b>Diagnostics</b>	LEDs (power, link status, data, data rate)	
<b>Ambient conditions</b>		
<b>Operating temperature</b>	0 °C to +60 °C	
<b>Storage/transport temperature</b>	-40 °C to +70 °C	
<b>Relative humidity (non-condensing)</b>	10% to 95%	
<b>MTBF</b>	138.5 years; MIL-HDBK 217F: Gb 25 °C	
<b>Mechanical construction</b>		
<b>Dimensions (W x H x D)</b>	25 mm x 114 mm x 79 mm	
<b>Mounting</b>	DIN Rail 35 mm	
<b>Weight</b>	113 g	
<b>Protection class</b>	IP 30	
<b>Mechanical stability</b>		
<b>IEC 60068-2-27 shock</b>	15 g, 11 ms duration, 18 shocks	
<b>IEC 60068-2-6 vibration</b>	3.5 mm, 3 Hz - 9 Hz, 10 cycles, 1 octave/min.; 1g, 9 Hz - 150 Hz, 10 cycles, 1 octave/min.	
<b>EMC interference immunity</b>		
<b>EN 61000-4-2 electrostatic discharge (ESD)</b>	6 kV contact discharge, 8 kV air discharge	
<b>EN 61000-4-3 electromagnetic field</b>	10 V/m (80 - 1000 MHz)	
<b>EN 61000-4-4 fast transients (burst)</b>	2 kV power line, 4 kV data line	
<b>EN 61000-4-5 surge voltage</b>	Power line: 2 kV (line/earth), 1 kV (line/line), 1 kV data line	
<b>EN 61000-4-6 conducted immunity</b>	10 V (150 kHz - 80 kHz)	
<b>EMC emitted immunity</b>		
<b>FCC CFR47 Part 15</b>	FCC CFR47 Part 15 Class A	
<b>EN 55022</b>	EN 55022 Class A	
<b>Approvals</b>		
<b>Safety of industrial control equipment</b>	cUL 508 (E175531)	



## HIRSCHMANN

A BELDEN BRAND

Industrial Ethernet:Unmanaged Industrial Ethernet Switches:SPIDER-Switches:SPIDER 3TX-TAP

**Scope of delivery and accessories**

<b>Scope of delivery</b>	Device, terminal block, operating manual
<b>Accessories to order separately</b>	Rail power supply RPS 15, RPS 30, RPS 80 EEC or RPS 120 EEC, 19" installation frame

The information published in the websites has been compiled as carefully as possible. It is subject to alteration without notice in technical as well as in price-related/commercial respect. The complete information and data were available on user documentation. Mandatory information can only be obtained by a concrete query.